

U1810B USB Coaxial Switch SPDT

DC to 18 GHz



Introduction

Description

The Keysight Technologies, Inc. U1810B is a USB-powered SPDT coaxial switch, operating from DC to 18 GHz, and supports the standard plug-and-play functionality of typical USB devices. The unique combination of excellent RF performance with the convenience of USB connectivity presents an invaluable alternative for users to increase the efficiency of their test systems. No additional power supply is required and the Type-N common input connector provides a rugged and robust connection with the instrument ports. A push-button on the switch casing allows for direct toggling of the two output ports without the need for any software interface. In addition, the bundled soft front panel provides an alternative virtual interface to control the U1810B. Users also have the option to control the switch through commonly used software programming platforms such as C#, C++, LabVIEW, VEE, etc.

Key Features and Benefits


- USB plug-and-play eliminates the need for additional power adapters or drivers, simplifies complex test setup
- Excellent insertion loss repeatability of 0.03 dB to 1 million cycles and 0.1 dB to 2 million cycles, ensures measurement accuracy
- 2 million cycles operating life, reduces cost-of-test and ensures reliability of the test system
- Excellent isolation (> 70 dB at 18 GHz), minimizes cross-talk between channels to ensure signal integrity
- Instant switch toggling via the push-button on the casing facilitates quick test setup validation



Using four U1810B's to extend a 4-port ENA to 8 ports to increase throughput

Applications

The U1810B USB switch is a single-pole double-throw (SPDT) relay which consists of one common port and two output ports. It routes signals from one input to two output paths. The following figure shows the SPDT relay schematics of an RF circuit state.



Compared to conventional switch designs where all the connector ports are on the same plane, Keysight's U1810B USB switch design helps users to simplify test setup without using additional RF cables. Figure 1 below shows a conventional switch connected to a measuring instrument. Both methods require extra RF cable(s) to be connected between the switch and the instrument. If a rigid cable is used, the length and bend angle of the cable has to be taken into consideration during the cable design. If a semi-rigid or flexible cable is used, the cable has to be fixed during measurement, any slight movement of the cable will change the mismatch and affect the measurement accuracy.




Figure 1. How a conventional switch is connected to a measuring instrument


With Keysight's U1810B switch design, the user can perform the same measurement without any additional RF cable (Figure 2). Hence, the user can avoid all the test setup issues caused by the additional RF cable.



Figure 2. How the Keysight U1810B USB switch is connected to a network analyzer

Using U1810B with a Network Analyzer

Below is an application example where the U1810B is used with a network analyzer to measure two devices under test (DUT) with 1 connection, either in frequency or time domain. Similarly, the U1810B can be used to switch between the DUT and the reference unit for calibration or compensation. In a traditional test calibration process, the user needs to remove the reference unit from the network analyzer after the calibration and connect the DUT to the network analyzer to complete a measurement. The U1810B helps to eliminate the time and resource to change the connection between the DUT and reference unit.




Using U1810B with Keysight's FieldFox Handheld RF Analyzer

At a cell site, the USB switch can be used to perform return loss, cable loss, and DFT (distance-to-fault) measurements on two cables.





Using U1810B with a Spectrum Analyzer

The USB switch can also direct connect to a spectrum analyzer to measure two DUT's concurrently, such as switching between two antennas for spectrum measurements.



Using U1810B with a Keysight's Wireless Communications Test Set

Mobile phone manufacturing test typically requires RF and non-RF testing. During non-RF testing, the wireless test set is idle. With the U1810B USB switch, it helps to reduce the idle time of the wireless test set by switching to DUT 2 for testing, before it switches back to DUT 1 to continue the RF test.



Specifications

Specifications refer to the performance standards or limits against which the U1810B is tested. Typical characteristics are included for additional information only and they are not specifications. These are denoted as “typical,” “nominal” or “approximate” and are printed in italic.

Frequency range	DC to 18 GHz
SWR	DC to 4 GHz: < 1.15 4 to 12.4 GHz: < 1.25 12.4 to 18 GHz: < 1.40
Insertion loss (dB, max)	$0.3 + (0.6/18)f$, where f is specified in GHz
Isolation (dB, min)	$90 - (30/26.5)f$, where f is specified in GHz
Life	2 million cycles
Switching time ¹	25 ms
Common connector	Type N (male)
Port 1/port 2 connector	SMA (female)
Maximum input RF power	
Hot switching	2 W CW, 100 W peak, 10 μs max pulse width, not to exceed 2 W average
Cold switching	See “Supplement Specifications (Cold Switching)”

1. < 35 ms for -25 to -5 °C

Absolute maximum rating

Parameter	Condition	Typical	Units
Rated voltage	–	5	V
Rated current	Switching	420	mA
	Non switching (Quiescent)	60	mA

Minimum system requirements

Parameter	Requirements
Interface	USB HID
Host operating system	32-bit operating system: Windows XP, Windows Vista, Windows 7 64-bit operating system: Windows Vista, Windows 7




Figure 3. Keysight U1810B typical return loss performance




Figure 4. Keysight U1810B typical insertion loss performance




Figure 5. Keysight U1810B typical isolation performance

Supplemental Specifications (cold switching)




Figure 6. Maximum incident CW power across frequency

Note:

- Cold switching only (NO hot switching)
- Ambient temperature of 75 °C or less
- Sea level (0.88 derating at 15,000 ft.)
- Load VSWR < 1.2 (see graph for derating above 1.2 VSWR)




Figure 7. Power derating factor versus VSWR

Environmental Specifications

The U1810B USB coaxial switch is designed to fully comply with Keysight's product operating environment specifications. The following are the summarized environmental specifications for this product.

Temperature		
Operating		-25 to +75 °C
Storage		-55 to +85 °C

Vibration		
Operating		0.21 grms, 5 to 500 Hz, 10 min/axis
Survival random		2.09 grms, 5 to 500 Hz, 10 min/axis
Swept sine		0.5 g, 5 to 500 Hz, 10 min/axis
Operating shock		Pulse duration < 3 ms, velocity 60 in/s
Transportation shock		Minimum 50 g

Humidity		
Operating/storage		15 to 95 % relative humidity

Altitude		
Operating/storage		15,000 ft/4.6 km

ESD immunity		
Direct discharge		8 kV
Air discharge		15 kV

Mechanical Dimensions

Mechanical dimensions	Figure 8 (below)
Weight	250 g
Shipping weight	0.88 kg




Figure 8. U1810B mechanical dimensions (dimensions are in millimeters, unless otherwise specified)

Ordering Information

U1810B USB Coaxial Switch, SPDT DC to 18 GHz

Related Literature

Keysight Bench and System Switching Products

Literature Number 5989-9872EN <http://literature.cdn.keysight.com/litweb/pdf/5989-9872EN.pdf>

Keysight RF and Microwave Switch Selection Guide

Literature Number 5989-6031EN <http://literature.cdn.keysight.com/litweb/pdf/5989-6031EN.pdf>

Keysight 11713B/C Attenuator/Switch Drivers Configuration Guide

Literature Number 5989-7277EN <http://literature.cdn.keysight.com/litweb/pdf/5989-7277EN.pdf>

Application Notes

Power Handling Capability of Electro-mechanical Switches

Literature Number 5989-6032EN <http://literature.cdn.keysight.com/litweb/pdf/5989-6032EN.pdf>

How Operating Life and Repeatability of Keysight's Electromechanical Switches Minimize System Uncertainty

Literature Number 5989-6085EN <http://literature.cdn.keysight.com/litweb/pdf/5989-6085EN.pdf>

Learn more at: www.keysight.com

For more information on Keysight Technologies' products, applications or services, please contact your local Keysight office. The complete list is available at:

www.keysight.com/find/contactus

